



CAM-Analog2.0

Set for wireless video transmission from analog CVI/TVI/AHD cameras up to 2Mpix

Resolution:	up to 2Mpix
Video standards:	TVI (Hikvision), CVI (Dahua, BCS), AHD (Samsung), CVBS
Wireless range:	500m Line of sight
Frequency	5.8GHz
Channel width:	20/40MHz
Number of working channels:	All / EU-area 8/2
Transmission power (CE)	25mW (14dBm) EIRP
Antenna	Directional, built-in, 45° working angle
OSD controls	NO
Audio	NO
Video	BNC 1Vp-p (75Ω)
Modulation	Analogue FM
Power	9-16V DC (Tx-800mA, Rx-500mA)
Installation	On the pole, using u-bolt
Working temperature	-20°C – 55°C
Dimensions	Tx: 152x103x60 [mm], Rx: 164x164x80 [mm]
Application	Outdoor IP66
Compliance with standards	CE, RoHS
Included	Transmitter and receiver
Klinger Finland Order number:	
Useful accessories	Power supply: ZS12V/1A, PTZ controls: CD04, Battery: iCAM-Battery230



Klinger Finland Oy

Tinankuja 3, 02430 Masala

Puhelin 010 400 1011 www.klinger.fi