





Rapidly Deployable

- User-friendly
- Quick installation
- Simple configuration



Reliable

- ► 24/7 operation
- Weatherproof
- Uninterrupted power supply



Movable

- ▶ Towable
- High mobility



Versatile

- Monitoring & Analytics
- Illuminating & Broadcasting
- Customization

Product Features Immediate · Safe · Intelligent



Rapid Deployment CCTV Trailer

Specifications

Trailer and Telescopic Mast			
Trailer Type	Single-axle Two-wheel Trailer		
Trailer Material	Steel		
Max. Towing Speed	40km/h		
Weight	~700kg		
Dimensions (Length * Width * Height)	2.5 * 1.1 * 1.3m (Trailer without telescopic mast) 2.5 * 1.1 * 2.0m (Trailer with retracted telescopic mast) 2.5 * 1.1 * 2.2m (Trailer with retracted telescopic mast and mast-top equipment) 2.5 * 1.8 * 6.0m (Trailer with extended telescopic mast and extracted solar panels) - operational state		
Mast Load/ Height	50kg (max.)/ 6m (max.)		
Mast Material/ Dynamics	Aluminium/ Pneumatic		
Build-in Cables	4-core-wire		
Operating Temperature	-10°C ~ 60 °C		
Power System			
Solar Panel Dimensions (Set of 3 panels)	1.3 * 0.7m (contracted) 1.3 * 1.8m (extracted)		
Solar Panel Power Output	3 * 100W (max.)		
Battery Type	Lead-acid		
Battery Dimensions	198 * 130 * 197mm/ unit		
Battery Capacity (Unit)	12V 36Ah		
Battery Pack Capacity (Consists of 4 batteries)	48V 36Ah *Max Quantity of Battery Packs in Trailer: 4 (16 battery units)		
Estimated Battery Lifetime	With 4 Battery packs (48V, 144Ah), no solar used @ 50W consumption: <130h (5-6 days)		
VAC Power Input	220V AC/ 50Hz (for charging only)		

Ordering Information

Ordering information		
Available Model	Description	
MVSL	Base 2-wheeled Rapid Deployment CCTV Trailer with Telescopic Mast	
Optional Accessories (to be purchased separately)		
BP1	Battery pack 48V 36Ah (consists of 4 batteries)	
SP1	3 x 100W Solar Panels	
PTZC1	2MP 20x optical zoom PTZ IR IP Camera	

FC1 1.3MP Fixed IP Camera

NVR1 4-ch Embedded NVR

FCHT Wiffi

T1 5GHz WiFi **T2** 3G/4G Router

^{*}Two-way audio, LED/ IR lights, motion/ vibration sensors and other customizable options are available. Please contact our Salespersons.

Light Rapid Deployment CCTV Cart

Specifications

Cart and Telescopic Mast		
Cart Type	Four-wheel standing cart	
Cart Material	Steel	
Weight	80kg	
Dimensions (Length * Width * Height)	75 x 50 x 110cm (without mast) 75 x 50 x 170cm (with mast) 75 x 50 x 400cm (with mast extended)	
Mast Load/ Height	5kg	
Mast Material/ Dynamics	Aluminium/ Pneumatic	
Build-in Cables	one cat6 cable	
Operating Temperature	-10°C ~ 60 °C	
Power System		
Battery Quantity	4 units max.	
Battery Type	lead-acid	
Battery Dimension	230 x 175 x 230mm	
Battery Capacity	12V 65Ah	
Estimated Battery Lifetime	With 4 Battery units @30W <100h (4 days)	
VAC power Input	220V AC/ 50Hz (for charging only)	

Ordering Information

Available Model	Description	
MVSS	Base 4-wheeled Light Rapid Deployment CCTV Cart with Telescopic Mast	
Optional Accessories (to be purchased separately)		
BU1	Battery unit 12V 65Ah	
PTZC2	2MP 20x optical zoom PTZ IR IP Camera	
FC1	1.3MP Fixed IP Camera	
T1	5GHz WiFi	
T2	3G/4G Router	

^{*}Two-way audio, LED/ IR lights, motion/ vibration sensors and other customizable options are available. Please contact our Salespersons.