


## SI200

A new Digital system from the Solartron Orbit stable! The SI 200 is an economical, dual channel solution with integral display that can be output to a PLC via ModBus, the most widely used network in the Industrial world. The SI 200 is part of Orbit ACS, a new line of Digital systems specially built for automation and process control.

- ▶ Modbus communication or Solartron ASCII Serial outputs
- ▶ High accuracy with Solartron's Real time Orbit error mapping
- ▶ 0.1  $\mu\text{m}$  display resolution
- ▶ High sampling speed 5 ms per reading
- ▶ Eliminated losses due to analogue to digital conversion via PLC connection
- ▶ User defined keypad functions
- ▶ Colour display LCD screen
- ▶ Discrete I/O
- ▶ Available with large number of integral transducers
- ▶ Mathematical Functions



*simply*  
**Modbus**




Solartron Metrology, the world leader in digital gauging probe innovation, introduces a new dual channel digital probe with integral display. which can be connected to any Solartron Digital probe to provide a two probe measurement system. Powered by a 24 VDC supply, the SI200 module can communicate using the industrial standard Modbus RTU (or ASCII) protocol, providing a simple connection to most PLCs Discrete Input and Output lines are also provided for simple interfacing and control.

The SI200 naturally comes with all of the standard metrology functions such as zero, preset and TIR. The unit can also be programmed to provide limit information.

The SI200 can perform standard mathematical functions such as A+B or A-B and show the result on the dual channel display.

Typical Application




FROM MEASUREMENT SI100 to PLC via MODBUS



FROM MEASUREMENT SI100 to PLC USING PRINT INPUT AND RS-232 SERIAL PORT

## Interfacing to the SI200

12	Input 4: Spare
11	Input 3: Print
10	Input 2: Preset
9	Input 1: Zero
8	Output supply In
7	Output 3
6	Output 2
5	Output 1
4	RS232RX MODBUS B
3	RS232TX MODBUS A
2	0V Power In Return
1	18 - 32 V Power In



Interfacing the SI200 is simple using the terminal connections on the rear of the module.

## Serial Output Options

The SI200 provides a standard Modbus interface, it can be user configured via the menu screens to use pins 3 and 4 as an RS232 interface. Once configured in RS232 Mode the user can select several different protocols offering compatibility with Solartron's SI3000, SI1500 and C55. This is for retrofit/replacement applications.

## Accessories

- +24 VDC Power Block and Mains Lead (2 m).
- Spare Mounting Modules.
- Firmware Upgrade Cable. (USB A to Mini B)

For 3D drawings please contact [sales.solartronmetrology@ametek.com](mailto:sales.solartronmetrology@ametek.com)


# Technical Specification

Performance	
Mathematics	MAXA-MINA, MAX B-MINB A+B, (A+B)/2, A-B, (A-B)/2
Accuracy	See Table
Keypad (5 keys)	
Navigation	▲Up, ▼Down, ◀Left ▶Right ■Enter
Functions	Print, Zero, Preset, and set up via menu
Type	Sealed membrane
Inputs and Outputs	
Serial	RS232 or RS485 Serial communications RS485 MODBUS RTU or ASCII
3 Discrete Outputs	HI, OK or LO Alerts (programmable)
Output Types	NPN, PNP or Logic
3 Discrete Inputs	Print, Zero, Preset,
1 Discrete Input	Configurable
Analogue Display One or Two channels	
Single Bar Scale	Analogue representation of reading Programmable

Note 1: A refers to the measurement made by the SI200  
B refers to the measurement made by the attached Digital probe

## SI200 with Standard Digital Gauging Probes

Axial Cable Outlet (probe)	SI200P/1	SI200P/2	SI200P/5	SI200P/10	SI200P/20
Radial Cable Outlet (probe)	SI200PR/1	SI200PR/2	SI200PR/5	SI200PR/10	SI200PR/20
Measurement Range (mm)	1	2	5	10	20
Probe Body Diameter			8h6		
Pre Travel (mm)			0.15		
Post travel			0.85		
Accuracy (% reading)	0.05	0.05	0.05	0.06	0.07
Repeatability			<0.15		
Resolution			<0.1		
Tip Force (N) at centre range			0.7±20%		



Note:  
Display can be rotated to accommodate different Mounting orientations

Digital LCD Display One or Two channels	mm	inches
Digital Measuring Range 1	0 to ±99.9999	0 to ±9.99999
Digital Measuring Range 2	0 to ±999.999	±99.9999
Digital Resolution range 1	0.0001	0.00001
Digital Resolution range 2	0.001	0.0001
Environmental		
Input Voltage	18 to 32 V	
Input Current (@24 V)	<70 mA	
Sealing: Transducer	IP65 to Fully Sealed Dependent on Type	
Sealing: Electronics	IP41 (top and front), (IP20 rear)	
Operating Temperature	+5 to +70 °C	
Storage Temperature	-20 to +80 °C	
Electrical Immunity	EN61000-6-2 and EN61326	
Electrical Emissions	EN61000-6-3 and EN61326	
Mechanical		
Standard Cable length	2 m (others available on request)	
Mounting	DIN rail	
Weight	300 g (nominal)	

The SI200 is available with many other Solartron transducers, such as mini probes and displacement sensors. Please contact your local sales representative or distributor.

### United Kingdom - Head Office

Solartron Metrology  
Steyning Way  
Bognor Regis  
West Sussex  
PO22 9ST  
Tel: +44 (0) 1243 833333  
Fax: +44 (0) 1243 833322  
Sales.solartronmetrology@ametek.com

### France

Solartron Metrology  
Rond-point de l'Espine des Champs  
Buroplus - Bat. D  
Elancourt 78990  
Tel: +33 (0)1 30 68 89 50  
Fax: +33 (0)1 30 68 89 59  
france.solartronmetrology@ametek.com

### Germany

Ametek GmbH  
Solartron Metrology Division  
Rudolf-Diesel-Strasse 16  
40670 Meerbusch  
Tel: +49 (0) 2159 9136 500  
Fax: +49 (0) 2159 9136 505  
vertrieb.solartron@ametek.de

### India

Ametek Instruments India Private Limited  
1st Floor, Left Wing  
Prestige Featherlite Tech Park  
Plot #148, EPIP II Phase  
Whitefield, Bengaluru 560 066  
Karnataka, India  
Tel: +91 80 6782 3200  
Fax: +91 80 6782 3232

### USA

Solartron Metrology  
USA Central Sales Office  
915 N. New Hope Road, Suite C  
Gastonia, NC 28054  
Tel: +1 800 873 5838  
Fax: +1 704 868 8466  
usasaes.solartronmetrology@ametek.com

### China

AMETEK Commercial Enterprise (Shanghai)  
Co. Ltd  
No. 1 AMETEK Road  
Ju Ting Economic Development Zone  
Shanghai 201615  
Tel: +86 21 5763 2509  
Fax: +86 21 5866 0969 Ext. 261/262  
china.solartronmetrology@ametek.com



Offices worldwide

Agent and distributor details available at  
[www.solartronmetrology.com](http://www.solartronmetrology.com)



Q 09540

Solartron pursues a policy of continuous development. Specifications in this document may therefore be changed without notice.

Datasheet 503085  
Issue 2  
EDCR 20227